

TECHNICAL DATA SHEET

Product:	ETIBOR-48 (Granular and Powder)
Synonyms:	Di-sodium Tetraborate Pentahydrate; Buffer Salt pH 9.18; Borax Pentahydrate; Sodium Borate Pentahydrate, 5 mol Borax
CAS#	12179-04-3
Formula:	$\text{Na}_2\text{B}_4\text{O}_7 \cdot 5\text{H}_2\text{O}$
Product Description:	Etibor-48 is a white, odorless crystalline granular or powder product. Etibor-48 is the most common form of sodium borate used in industry. It is mildly alkaline. The most tangible advantage of using Etibor-48 is, besides having comparable physico-chemical aspects as that of Borax Decahydrate, Etibor-48 has relatively higher Boron content per unit mass compared to Borax Decahydrate. Etibor-48 is also less hygroscopic. It is mildly alkaline in solution.
Packaging:	Etibor-48 is available in 25 kg (55 lb.) multilayer paper bags, 1000 kg (2200 lb.) bulk bags and bulk loose powders.
Applications:	<ul style="list-style-type: none">- Fluxing agent- Water Softener and Buffering Agent- Soaps and Detergent formulations- Agriculture- Pesticide formulations- Corrosion Inhibition- Glass and Ceramics- Fiberglass Insulations- Lubricant- Antifreeze- Adhesives- Flame retardant
Precautions:	Etibor-48 is chemically stable, however, it is advised to store Etibor-48 under dry, cool and steady temperature conditions. During storage and transport avoid any wide variation in temperature. With temperature cycling and exposure to humid environment, Etibor-48 may undergo inter-particle bridging or caking, which may impair material flow.

Typical properties of Etibor-48:

Property	Typical Value
Appearance	Granular Powder
Color	White
Bulk Density	55-65 lb / ft ³
Specific Gravity	1.88
Solubility in water at 25°C, 50°C and 100°C	4.4%, 13.7% and 50% respectively
Solubility in propylene glycol at 25°C	21.5%
pH of saturated aqueous solution at 20°C	9.2

Chemical Analysis					
Component	Unit	Specification Granular (min-max)	Typical Value Granular	Specification Powder (min-max)	Typical Value Powder
B ₂ O ₃	%	48.0– 49.35%	49	47.8 – 49.0 %	48
Na ₂ O	%	21.37 - 21.95 %	21.6	21.36 – 21.81 %	21.6
SO ₄	ppm	135 max.	108	200 max.	120
Fe	ppm	3 max.	2	3 max.	2
Cl	ppm	70 max.	50	70 max.	55
Water Insoluble	ppm	150 max.	115	150 max.	125
Purity	%	99.90 min.	100	99.90 min.	100

Dry Sieve Analysis						
Size	US Mesh	Unit	Specification Granular	Typical Value Granular	Specification Powder	Typical Value Powder
+ 1.680 mm	12	%	-	0.1	-	-
+ 1.180 mm	16	%	4.0 max.	2.0	2.0 max.	0.1
+ 0.85 mm	20	%	-	8.0	-	-
+ 0.60 mm	30	%	-	18.0	-	2.0
+ 0.15 mm	100	%	-	60.0	-	-
+ 0.075 mm	200	%	-	9.0	-	84.0
- 0.075 mm	- 200	%	5.0 max	3.0	50.0 max.	14.0

This TDS is to provide all necessary information about the product that customers must be aware of. However, excepting the given specifications, other information provided in this TDS do not form part of any selling specification. Information contained in this TDS is correct to the best of ETIMINE's knowledge and understanding based on available information. However, no warranty of merchantability or any other warranty, expressed or implied, with respect to such information can be made, and no liability resulting from its use can be assumed. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ETIMINE USA, INC be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ETIMINE USA has been advised of the possibility of such damages.